

PROSIB PROTECT 10

Polymer Sealer

DESCRIPTION

Polymer sealer containing polyurethane

Care treatment

Reduces dirt adhesion

Easy to maintain

Manufacturer

SIB, Sociedade Industrial
De Britagem De Pedra, LDA

DESCRIPTION:

PROSIB PROTECT 10 is a polymer sealer containing polyurethane for the care treatment of resilient floors and mineral floors sealed with PROSIB 777 and PROSIB 999, that creates an elastic, anti-slip matte film, reducing dirt adhesion and facilitates routine cleaning.

PROSIB PROTECT 10 is also suitable for refreshing floors with a PU factory finish and renovating care-film in a high speed process.

FIELDS OF APPLICATION:

PROSIB PROTECT 20 can be used on mineral floors protected with PROSIB 777 and PROSIB 999, as well as on vinyl and linoleum floors. Using on rubber floors is possible only under certain circumstances and should be checked before use.

TECHNICAL PROPERTIES AND CHARACTERISTICS:

Consumption	Initial protection/refreshing - 1 l per 50 m ²
	Daily cleaning - 0,1 l per 50 m ²
pH	7,5 - 8

SUPPORT PREPARATION:

The surface must be dry and clean, free from dust, oils, dirt, salts, other finishes grease and loose particles.

Residues from curing compounds, sealers, upcoming moist, acids, salts and other compounds may affect the sealer.

Do not use prep cleaners containing soy or d-Limonene as these interfere with adhesion of water-based sealers.

Do not apply over concrete treated with densifiers without first testing their effectiveness. It may contain components that reject/repel water-based products.

Before the sealer application, use PROSIB CLEAN RC-50 in a 1 to 4% dilution in water to wash the floor. Then vacuum and let the floor dry.

APPLICATION:

Shake PROSIB PROTECT 10 vigorously and apply one coat evenly at 15 to 30 °C air temperature (59 to 86 °F) onto the surface with a non-felting wiper mop.

Let dry overnight before use.

DAILY CLEANING:

Add 50 ml of PROSIB PROTECT 10 to a bucket with 8 to 10 l of water. Turn off under-floor central heating before work.

Note: When applying the product undiluted, avoid strong sunlight and drafts. Turn off under-floor central heating before work.

PRODUCTION, PACKAGING, STORAGE AND EXPIRY DATE:

PROSIB PROTECT 10 is available in 5 l canister.

The product can be stored in its original packaging for 12 months in a dry place at a controlled temperature (not below 0 °C/32 °F). Recommended storage is between 10 and 25 °C (50 and 77 °F).

FREEZE WARNING. Keep away from freezing temperatures.

COMPLEMENTARY INFORMATION:

Surface preparation is essential for a good result.

Always make a small sample to see how the sealer performs. Several conditions influence on a good reaction of this product on the surface.

Low temperatures, increased air humidity and poor ventilation can significantly extend the drying time.

The evaporation of water can be accelerated by ventilation.

The area should not be wet-mopped in the first 3 days afterwards.

Refrain from placing rugs in the first 10 to 14 days. Carefully place the furniture.

Covers for protection during further work should be applied after 3 days at the earliest. We recommend breathable and slip-protected covers.

Unless covering is only for short-term protection, full-surface covering is recommended. To avoid infiltration, joints of masking units should be sealed with a vapour-diffusion-open adhesive tape. Avoid applying adhesive tape to the freshly painted substrates.

Please pay attention to the printed batch number. Only use products with the same batch number in one layer. In the case of a different batch, mix this in a separate container before using.

Before using SIB products, consult applicable data sheets, protocols, product labels and safety data sheets.

Wash tools with clean water immediately after using them.

It is the user's responsibility to read the instructions and warnings for any SIB product before using it. The valid updated data sheet can be found at www.sibland.company.

WARNING:

Use suitable PPE: impermeable gloves, boots and protective goggles and mask.

Avoid contact with skin and eyes; prolonged contact may cause skin irritation.

Do not drink, eat or smoke while handling the product.

Non-flammable and non-explosive product.

See the complete Product Safety Data Sheet.

LIMITED WARRANTY:

SIB - Sociedade Industrial De Britagem De Pedra, LDA warrants its materials to be of good quality and, at its option, will replace or refund the purchase price of any material proven to be defective within one (1) year from date of purchase. The above remedies shall be the limit of SIB's responsibility. Except for the foregoing, all warranties expressed or implied, including merchantability and fitness for a particular purpose, are excluded. SIB shall not be liable for any consequential, incidental, or special damages arising directly or indirectly from the use of the materials. In order to obtain all the results and technical properties of the products, all SIB specifications and instructions on transport, storage, use, application and maintenance must be fully complied with, otherwise, SIB does not guarantee the technical results and properties of the products.